

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 2003-005751

(43)Date of publication of application : 08.01.2003

(51)Int.Cl.

G10H 1/32
G10H 1/043
G10H 3/18

(21)Application number : 2001-192870

(71)Applicant : HOSHINO GAKKI CO LTD

(22)Date of filing : 26.06.2001


(72)Inventor : HIRAYAMA SHINJIRO

(54) TREMOLO DEVICE FOR STRINGED INSTRUMENT

(57)Abstract:

PROBLEM TO BE SOLVED: To provide a tremolo device for stringed instrument which is capable of minimizing the deviation in tuning after tremolo operation, etc.

SOLUTION: This tremolo device 1 for stringed instrument includes a tremolo body 10 having a tremolo block 40, an arm 50, a back mechanism base 61, a first bearing section 62 and second bearing section 63, a slide shaft section 70, a positioning stopper 71, a slide block 75, a movable stopper 80 having a front part 81 abutable and separable on and from the slide block and a rear part 82 abutable and separable on and from the positioning stopper, a connecting link 85 for connecting the tremolo block and the slide block, a first spring 90 spread between the rear mechanism base and the slide block and a second spring 95 spread between the front part of the movable stopper and the second bearing section.



LEGAL STATUS

[Date of request for examination]

31.01.2003

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]